



KBC Care instructions

Care instructions for high gloss laminate fronts

Fronts with a high gloss surface are characterised by an excellent brilliance which is created with the aid of a high gloss polymer film.

The fronts are covered with a protective film in order to ensure that they do not suffer any damage either during processing or transport. This film should only be removed during the last working stage of installation.

High gloss fronts are characterised by their very easy cleaning, since the surface is completely sealed. Any soiling that adheres can therefore be easily removed without much effort and without use of chemical products.

It is essential to ensure that the cleaning materials used (cloths, sponges, etc.) are extremely clean.

Any mineral soiling present in cleaning materials, such as grains of sand or dust particles may result in scratching of the surface and must therefore not be used.

The manufacturer cannot undertake any warranty for this type of traces of use.

The cleaning materials used – preferably cotton cloths (not microfibre cloths!) – must be thoroughly cleaned and rinsed beforehand. If mineral or metallic particles are absorbed during cleaning, the cleaning materials must be constantly rinsed in order to ensure that the dust particles do not leave any marks on the high gloss surface.

Small microscopic traces of use may result. These are more or less noticeable according to colour and incidence of light. They do not impair the functional value and are unavoidable in the long term as with all high gloss surfaces on cars, glasses or other furniture surfaces.

This type of traces of use does not constitute any grounds for complaint.